

Tørris - bruksområder

Transport av farmasøytiske produkter



The image shows a product brochure for the TempCell Shipper. It features a table of specifications, a temperature profile graph, and a list of features and benefits.

Specification	TempCell 3	TempCell 10	TempCell 20
External dimensions L x W x H (mm)	360 x 475 x 475	610 x 675 x 575	1110 x 1170 x 575
Internal padded space (mm)	360 x 230 x 230	360 x 230 x 230	360 x 230 x 230
Internal padded volume (liters)	3	13	20
Net weight (kg)	20	25.5	38.5
Temperature range (°C)	+2 to +8 / +25 to +25	+2 to +8 / +25 to +25	+2 to +8 / +25 to +25
Relative humidity	20%	20%	20%

Summer Temperature Profile
Validation Results
TempCell 10 Shipper - 2°C to +8°C
- 10 x 100mm Flat Pack (100mm x 100mm x 100mm)
- 100mm x 100mm x 100mm

Features & Benefits

- Up to 120 hours protection for 2 to 10°C and 10 to 25°C products
- High performance Extruded Polystyrene (EPS) insulation
- 3 lock offering 1, 10 and 18 lines of padded space
- Multiple controller/label provides versatility of use
- Robust construction ensures built-in sustainability
- 100% recyclable

Softbox
Sustainable. Smart. Secure. Shipping Solutions.

